



| MARK | DATE | REVISION | REVISER | APP.BY |
|------|------|----------|---------|--------|
| ① | | | | |
| ② | | | | |
| ③ | | | | |

| | | | | | | |
|------------------|-----------|---------|---|----|-------------|--|
| MODEL NO | | | SKMPLR | | | |
| MATERIAL | | | HOUSING-PC | | | |
| | | | LENS-PC | | | |
| | | | REFLECTOR-PC/SUS | | | |
| COLOR OF LENS | | | RED(), AMBER(), GREEN(), BLUE() | | | |
| REV. PER MIN. | | | 120 ~ 140 | | | |
| USE VOLT. | POWER LED | CURRENT | DC12V | 1W | MAX. 0.422A | |
| | | | DC24V | | MAX. 0.266A | |
| PROTECTION GRADE | | | WATER & DUST PROOF IP54 | | | |
| CABLE ENTRY | | | ø10 LEAD HOLE | | | |
| COLOR OF HOUSING | | | MAKER STANDARD | | | |
| ACTION | | | POWER LED REVOLVING WARNING LIGHT | | | |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | | SURFACE FINISH | | - | - | - | - | 1 | - |
|--------------------------------|----------|--------|------|--------|--------|----------------|--|--|----------|-------------|---------|------|------------|
| FOR LINEAR DIMENSIONS | | f | m | Ⓢ | v | | | Nr. | DWG. NO. | TITLE/ NAME | MAT'L | QTY | REFERENCE |
| | 0.5~3 | | | ±0.2 | - | | | DSND BY | CHKD BY | CHKD BY | APRV BY | VIEW | DATE |
| | 3~6 | ±0.05 | ±0.1 | ±0.3 | ±0.5 | | | S.H.KIM | J.H.PARK | | J.K.HAN | 3 | 2016.08.30 |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 | | | <div>SKMPLR OUTLINE DRAWING</div> <div>Qlight</div> | | | | | |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 | | | | | | | | |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 | | | | | | | | |
| FOR ANGULAR DIMENSIONS | 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | | | <div>SKMPLR OUT</div> | | | | | |
| | 0~10 | ±1° | | ±1°30' | ±3° | | | | | | | | |
| | 10~50 | ±0°30' | | ±1° | ±2° | | | <div>SCALE N/S</div> <div>SIZE A4</div> <div>REV 00</div> <div>SHEET 1/1</div> | | | | | |
| | 50~120 | ±0°20' | | ±0°30' | ±1° | | | | | | | | |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' | | | | | | | | |