



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S150U-FT			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	1.545A	
			DC24V		0.766A	
			AC110V		0.204A	
			AC220V		0.102A	
VOLUME			MAX. 90dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.		TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1		TITLE S150U-FT OUTLINE DRAWING		DWG. NO. S150U-FT_OUT					
	30~120	±0.15	±0.3	±0.8	±1.5					SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°									
	10~50	±0°30'		±1°	±2°									
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									

A4(297X210)