



FITTING HOLES(SCALE 3:1)

MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			Q80LW			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			BRACKET-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60~80			
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.08W	MAX. 0.190A	
			AC110V ~ 220V		MAX. 0.052A	
VOLUME			MAX 80dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65			
CABLE ENTRY			ø23 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE Q80LW OUTLINE DRAWING		MODEL Q80LW				
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. Q80LW_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 00
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

A4(297X210)