



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			S180R-FT			
MATERIAL			HOUSING-SUS			
			LENS-AS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BLUB	CURRENT	DC12V	35W	MAX. 3.077A	
			DC24V		MAX. 1.544A	
			AC110V		MAX. 0.388A	
			AC220V		MAX. 0.194A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-								
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE								
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30								
	3~6			±0.3	±0.5															
	6~30	±0.1	±0.2	±0.5	±1		TITLE S180R-FT OUTLINE DRAWING			MODEL S180R-FT										
	30~120	±0.15	±0.3	±0.8	±1.5															
	120~400	±0.2	±0.5	±1.2	±2.5															
400~1000	±0.3	±0.8	±2	±4																
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'								±3°	DWG. NO. S180R-FT_OUT							
	10~50	±0°30'		±1°								±2°								
	50~120	±0°20'		±0°30'								±1°	SCALE N/S		SIZE A4		REV 00		SHEET 1/1	
	120~400	±0°10'		±0°13'								±0°30'								

A4(297X210)