



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QWL20			
MATERIAL		BODY-AL			
		LENS-PC			
		BRACKET-SUS			
COLOR OF LENS		TRANSLUCENT			
USE VOLT.	LED	CURRENT	DC12V~24V	CHIP LED	MAX.1.0A
PROTECTION GRADE		WATER & DUST PROOF IP67			
CABLE ENTRY		φ7			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
	400~1000	±0.3	±0.8	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±1°	±3°
	10~50	±0°30'	±1°	±1°	±2°
	50~120	±0°20'	±0°30'	±1°	±1°
	120~400	±0°10'	±0°13'	±0°30'	±0°30'

SURFACE FINISH

1	-	-	-	-	-
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
Y.H.JOO			J.K.HAN	3	2020.07.10
TITLE			MODEL		
QWL20 OUTLINE DRAWING			QWL20		
			DWG. NO.		
			QWL20_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		