



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		S60ADH		
MATERIAL		HOUSING-ABS		
		COVER-ABS		
USE VOLT.	CURRENT	DC12V	MAX. 0.083A	
		DC24V	MAX. 0.042A	
		AC110V	MAX. 0.016A	
		AC220V	MAX. 0.008A	
VOLUME		MAX. 100dB at 1m		
PROTECTION GRADE		WATER & DUST PROOF IP54		
CABLE ENTRY		10 X 10		
COLOR OF HOUSING		MAKER STANDARD		

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
	400~1000	±0.3	±0.8	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±2°	±4°
	10~50	±0°30'	±1°	±1°30'	±3°
	50~120	±0°20'	±1°	±2°	±2°
	120~400	±0°10'	±1°	±2°	±1°

SURFACE FINISH	-	-	-	-	1	-	
	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	DSND BY S.H.KIM		CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	TITLE S60ADH OUTLINE DRAWING				MODEL S60ADH		
					DWG. NO. S60ADH_OUT		
					SCALE N/S	SIZE A4	REV 00