


MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO	S100SM				
MATERIAL	HOUSING-ABS				
	LENS-AS				
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()				
FLASHES PER MIN.	60 ~ 80				
USE VOLT.	XENON	CURRENT	DC12V ~ DC24V	6W	MAX. 1.000A
PROTECTION GRADE	WATER & DUST PROOF IP54				
CABLE ENTRY	10 LEAD HOLE				
COLOR OF HOUSING	MAKER STANDARD				
ACTION	XENON LAMP STROBE LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE S100SM OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL S100SM					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. S100SM_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

A4(297X210)