




MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STG60L/ L-BZ/ STG60LF/ LF-BZ			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			PIPE-AL			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE(), WHITE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	AC/DC12V	0.5W	0.085A/LAYER1	
			AC/DC24V		0.060A/LAYER1	
			AC110V		MAX. 0.050A/LAYER1	
			AC220V			
VOLUME			MAX. 85dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65 (BZ TYPE-IP54)			
CABLE ENTRY			ø9.5 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

LAYER	L1	L2	L3
1	333	353	421
2	363	383	451
3	393	413	481
4	423	443	511
5	453	473	541

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	⊙	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.15	±0.3	±0.8	±1.5
	400~1000	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±0.3	±0.8	±2	±4
	10~50	±1°	±1°30'	±1°30'	±3°
	50~120	±0°30'	±1°	±1°	±2°
	120~400	±0°20'	±0°30'	±0°30'	±1°
	120~400	±0°10'	±0°13'	±0°13'	±0°30'

SURFACE FINISH	-		-		1		-	
	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE		
	Y.H.JOO			J.K.HAN	3	2024.10.24		
	TITLE STG60L SERIES OUTLINE DRAWING				MODEL STG60L SERIES			
				DWG. NO. STG60L SERIES-OUT				
				SCALE	SIZE	REV	SHEET	
				N/S	A4	00	1/1	

