



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL No.	SLP5130-R
MATERIAL	HEAD & BODY - DIE CAST AL BOLT,NUT,ROD & ETC. - SUS304
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d II C T6 / Ex tb IIIC T85°C WATER & DUST PROOF - IP66
CABLE ENTRY	STANDARD - NPT 1/2 OPTION - NPT 3/4
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC
CERTIFICATE	ATEX

■ Operating Characteristics

OF max.g	150
RF min.g	25
PT	25° ± 5°
MD max.	10°
TT min	40°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	MODEL J.K.HAN	VIEW 3	DATE 2012.01.27	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SLP5130-R-OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							