




※ *(227) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			PSSHD2L				
MATERIAL			HOUSING-AL				
			LENS-PC				
			REFLECTOR-HEAT RESISTING ABS				
			PROTECTION CAGE-SUS316L				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
FLASHING PER MIN.			60 ~ 80				
USE VOLT.	LED	CURRENT	DC12V		0.08W	MAX. 4.722A	
			DC24V			MAX. 2.188A	
			AC110V			MAX. 0.513A	
			AC220V			MAX. 0.256A	
PROTECTION GRADE			WATER & DUST PROOF IP66				
CABLE ENTRY			1/2" PF				
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2				
ACTION			LED STEADY/ FLASHING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	PSSHD2L OUTLINE DRAWING			PSSHD2L			
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	PSSHD2L_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			SCALE	SIZE	REV	SHEET	
	10~50	±0°30'		±1°	±2°			N/S	A4	00	1/1	
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

A4(297X210)