




MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		QLEX-SLM-250(PL)	
MATERIAL		HOUSING ( SIDE COVER ) - AL	
		HOUSING ( END COVER ) - AL	
		LENS ( GLOBE ) - PC	
COLOR OF LENS		TRANSLUCENT	
USE VOLT.	CURRENT	DC24V	MAX. 0.37A
PROTECTION GRADE		Ex d IIC T6 IP66/IP67	
CABLE ENTRY		M12xP1.5	



1. POWER CABLE  
- UL2464-AWG18(0.75sq)-3C-900mm

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH	-	-	-	-	1	-	
	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
	DSND BY J.Y. KIM	CHKD BY Y.H. JOO	CHKD BY 	APRV BY J.K. HAN	VIEW 3	DATE 2020.07.22	
	TITLE QLEX-SLM-250(PL) LAYOUT			MODEL QLEX SERISE			
				DWG. NO. QLEX -SLM-250-OUT			
				SCALE N/S	SIZE A4	REV 00	SHEET 1/1