

QAT80L / QAT80ML



QAT80L

Built-in buzzer output holes formed on the housing of the product



PRODUCT SPECIFICATION

QAT80L | QAT80ML

Materials Lens-PC, Housing-PA66, Pole-Al
Ambient operating temperature $-30^{\circ}\text{C} \leq T_{\text{a}} \leq +50^{\circ}\text{C}$
Volume Max.95dB at 1m
Protection rating IP65
Flashing rate 60-80/min
Compliant with RoHS directive

- LED Steady/Flashing Tower Lights
- Long product lifetime of over 20,000 hours with the application of a high intensity multiple color LED light source
- Built in 2 tone buzzer, Sound output according to LED color(Max.95dB at 1m).
- Standard model and built-in buzzer model can be used by selecting the specifications suitable for the operating environment.

QAT80L LED Steady/Flashing Tower Lights

Model number	Layers	Voltage	Certificates	Weight	Color
QAT80L Steady				0.50Kg	
QAT80L-BZ Steady w/ built-in buzzer	3	DC12V-24V	CE	1.10Kg	● R-Red ● A-Amber ● G-Green
QAT80LF Steady/Flashing				0.50Kg	
QAT80LF-BZ Steady/Flashing w/ built-in buzzer				1.10Kg	

- ※ DC type model has a free-voltage range of 10V-30V.
- ※ CE Compliant: DC24V

Light source/buzzer current(based on 1 layer)


Voltage	DC12V-24V
Light source current(1 layer)	Max.200mA
Buzzer current	Max.50mA

Selectable sound patterns

Built-in sound	Sound	Channel	Volume
1 buzzer sound	prolonged (beep)	Ch1	Max.95dB
2 buzzer sound	staccato (beep, beep, beep)	Ch2	

Technical Diagram

Units : mm



Mounting bracket

Standard	LB24	LW24	QZ24	SZ24	QL24	SL24
Steel	Steel	ABS	ABS	Al	ABS	Al

※ Please refer to [Tower Light Mounting bracket] on this catalogue for detailed dimensions

Ordering Specifications

QAT80L	-	3	-	12/24	-	RAG	-	LW24
[Model number]		[Layers]		[Voltage]		[Color]		[Bracket]
QAT80L QAT80L-BZ QAT80LF QAT80LF-BZ		3-3 Layers		12/24-DC12V-24V		● R-Red ● A-Amber ● G-Green		· None-Standard · Bracket · LB24 · LW24 · QZ24 · SZ24 · QL24 · SL24



QAT80ML LED Steady/Flashing Tower Lights

Model number	Layers	Voltage	Certificates	Weight	Color
QAT80ML Steady				0.50Kg	
QAT80ML-BZ Steady w/ built-in buzzer	3	DC12V-24V	CE	0.62Kg	<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green
QAT80MLF Steady/Flashing				0.50Kg	
QAT80MLF-BZ Steady/Flashing w/ built-in buzzer				0.62Kg	

※ DC type model has a free-voltage range of 10V-30V.
 ※ CE Compliant: DC24V



QAT80ML

Light source/buzzer current(based on 1 layer)

Voltage	DC12V-24V
Light source current(1 layer)	Max.200mA
Buzzer current	Max.50mA

Built-in buzzer output holes formed on the housing of the product




Selectable sound patterns

Built-in sound	Sound	Channel	Volume
1 buzzer sound	prolonged (beep)	Ch1	Max.95dB
2 buzzer sound	staccato (beep, beep, beep)	Ch2	

Technical Diagram


Units : mm

·QAT80ML



Wiring Instructions(External Contact)

·QAT80L / QAT80ML



Ordering Specifications

QAT80ML	-	3	-	12/24	-	RAG
[Model number]		[Layers]		[Voltage]		[Color]
QAT80ML QAT80ML-BZ QAT80MLF QAT80MLF-BZ		3-3 Layers		12/24-DC12V-24V		<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green