



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			Q100L		
MATERIAL			HOUSING-ABS		
			LENS-PC		
			-		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
FLASHES PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.08W	MAX. 0.255A
			AC110V ~ 220V		MAX. 0.067A
VOLUME			MAX. 80dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP65		
CABLE ENTRY			ø9 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STEADY/FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	⌀	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3			±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			Q100L OUTLINE DRAWING 					
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	0~10			±2	±4			Q100L OUTLINE DRAWING 					
	10~50			±1°	±2°								
	50~120			±0°30'	±1°			Q100L_OUT					
	120~400			±0°10'	±0°30'								
								SCALE	SIZE	REV	SHEET		
								N/S	A4	00	1/1		