

SESA-TI Series

Explosion proof Signal Beacon and Electronic Sounder combinations



SESALR-TI



SESAL-TI

PRODUCT SPECIFICATION

SESALR-TI | SESAL-TI
SESAS-TI | SESA-TI

Materials Lens-Tempered glass, Filter-PC, Housing-AI, Protection cage-ST316L, Reflector-PC, Reflector-Heat resistant ABS

Ambient operating temperature

-40°C ≤ Tamb ≤ +60°C

Protection rating

IECEX - Ex db IIC T6 Gb, IP66

ATEX - Ex II 2G Ex db IIC T6 Gb, IP66

Sound volume Max.118dB at 1m(Volume adjustable)

Housing standard color MUNSSELL No. 7.5BG 7/2

- Large explosion proof Signal Beacon and Electronic Sounder combinations
- Telephone Initiated signal beacon & sounder triggers built-in alarm sound that is activated by 25Hz telephone ring signal
- Highly noticeable telephone alarm in noisy environment
- Telephone line(2 LINE) is connected to PSTN telephone line
- A variety of light sources and sound selections to fit your sophisticated application needs
- Aluminum housing provides excellent durability
- Fully enclosed structure with protection rating of IP66
- Integrated housing and terminal box model
- Rated power when telephone lines are not in use: 45VDC - 55VDC
- Rated power when telephone rings : AC25V-AC120V, Frequency 15-55Hz

SESALR-TI LED Revolving Signal Beacon & Electronic Sounder Combination

Model number	Voltage	Current	Sound pattern and volume	Certificates	Weight	Color
SESALR-TI	DC24V	1.16A	·WS-5 Warning sounds: Max.118dB ·WP-5 Special warning sounds: Max.118dB	IECEX	8.31kg	● R-Red
	AC120V	300mA	·WM-5 Melodies: Max.118dB ·WA-5 Alarms: Max.116dB		7.92kg	● A-Amber ● G-Green
	AC230V	175mA	·WV-5 Customizable voices: 110-115dB	ATEX	7.92kg	● B-Blue

- Excellent omni-directional visibility with LED light collecting system and special multifaceted reflector
- Revolving speed: 120-140RPM

SESAL-TI LED Steady/Flashing Signal Light and Electric Horn Combination

Model number	Voltage	Current	Sound pattern and volume	Certificates	Weight	Color
SESAL-TI	DC24V	1.4A	·WS-5 Warning sounds: Max.118dB ·WP-5 Special warning sounds: Max.118dB	IECEX	8.42kg	● R-Red
	AC120V	320mA	·WM-5 Melodies: Max.118dB ·WA-5 Alarms: Max.116dB		9.02kg	● A-Amber ● G-Green
	AC230V	170mA	·WV-5 Customizable voices: 110-115dB	ATEX	9.02kg	● B-Blue

- Long-lasting high intensity LED light source, Suitable for applications where bulb replacement is hard
- Flashing rate: 60-80 flashes/min(Built-in steady/flashing selection switch)

※ Max.built-in volume feature is based on WS, WP-Ch1 / WM-Ch5 / WA-Ch5.

※ In case of customized WV 5 tone type, there may be difference of volume depending on user's audio file type.



SESAS-TI Xenon Strobe Signal Light and Electric Horn Combination

Model number	Voltage	Current	Xenon lamp			Certificates	Weight	Color	Color
			Spec	Standard	Parts no				
SESAS-TI	DC24V	1.4A	EUB0641 200V -1A(G) -550V U type	48	·WS-5 Warning sounds : Max.118dB ·WP-5 Special warning sounds: Max.118dB ·WM-5 Melodies : Max.118dB ·WA-5 Alarms: Max.116dB ·WV-5 Customizable voices: 110-115dB	IECEx ATEX	8.45kg	● R-Red	
	AC120V	300mA					8.86kg	● A-Amber	
	AC230V	190mA					8.86kg	● G-Green	● B-Blue

- Lamp connector fastening structure allows for convenient lamp replacement
- Excellent long-distance visibility with strong strobe signal diffusion
- Flashing rate: 60-80 flashes/min



SESAS-TI

SESA-TI Bulb Revolving Signal Beacon and Electronic Sounder Combination

Model number	Voltage	Current	Bulb			Certificates	Weight	Color	Color
			Spec	Standard	Parts no				
SESA-TI	DC24V	1.45A	24V15W	G23 15S	18	·WS-5 Warning sounds : Max.118dB ·WP-5 Special warning sounds: Max.118dB ·WM-5 Melodies : Max.118dB ·WA-5 Alarms: Max.116dB ·WV-5 Customizable voices: 110-115dB	IECEx ATEX	8.57kg	● R-Red
	AC120V	370mA	12V15W	G23 15S	17			9.27kg	● A-Amber
	AC230V	190mA	12V15W	G23 15S	17			9.27kg	● G-Green


- Excellent diffusion effect with special multifaceted reflector
- Revolving speed: 120-140RPM
- ※ Max.built-in volume feature is based on WS, WP-Ch1 / WM-Ch5 / WA-Ch5.
- ※ In case of customized WV 5 tone type, there may be difference of volume depending on user's audio file type.




SESA-TI

Technical Diagram · SESALR-TI / SESAL-TI / SESAS-TI / SESA-TI

Units: mm



- Standard Type: Select sound using the switch inside of the unit. When you turn on the dip switch for each channel, the designated sound will be played.



Ordering Specification

SESAS	-	WS	-	230	-	R	-	TI
[Model number] SESALR SESAL SESAS SESA		[Sound] WS-Warning sounds WP-Special warning sounds WM-Melodies WA-Alarms WV-Customizable voices		[Voltage] 24-DC24V 120-AC120V 230-AC230V		[Color] ● R-Red ● A-Amber ● G-Green ● B-Blue		[Telephone Initiated] TI-Telephone Initiated

Customization

- Explosion proof cable gland attached type available (Standard type does not come with explosion proof cable gland)
- 2 ways cable entries
- Customized cable entry (3/4" NPT, M20×1.5, M25×1.5) available