



S150RL / S150RS



S150RL-FT / S150RS-FT

## PRODUCT SPECIFICATION

S150RL | S150RS

**Materials** Lens-PC, Housing-STS,  
Reflector-Heat resistant ABS, Mounting bracket-STS316L  
**Ambient operating temperature** -30°C to +50°C  
**Protection rating** IP44  
**Flashing rate** 60-80/min

- Stainless Steel(STS) housing allows excellent anti-corrosiveness and durability
- Can select between standard and built-in buzzer type depending on installation environment
- Mounting bracket allows convenient installation in case of XXX-FT typ

### S150RL / S150RL-FT LED Steady/Flashing Signal Light

Model number	Voltage	Current	Certificates	Weight	Color
S150RL	DC12V-24V	Max.300mA	-	0.64kg	● R-Red
S150RL-FT	AC110V	70mA		0.92kg	● A-Amber
	AC220V	35mA		0.92kg	● G-Green ● B-Blue

- Built-in switch for selection between steady and flashing mode

### S150RS / S150RS-FT Xenon Lamp Strobe Signal Lights


Model number	Voltage	Current	Xenon lamp			Certificates	Weight	Color
			Spec	Standard	Parts no			
S150RS	DC12V-24V	Max. 1.3A	200V	EUB0641 -1A(G)	48	-	0.68kg	● R-Red
S150RS-FT	AC110V	160mA	-550V	U Type			0.66kg	● A-Amber
	AC220V	140mA					0.66kg	● G-Green ● B-Blue

- Connector type lamp socket allows convenient lamp replacement


## Technical Diagram

Units: mm

·S150RL / S150RS



·S150RL-FT / S150RS-FT



## Wiring Instructions

- External Power line - UL1015 AWG18(0.75sq) x 2C 400mm
- This product can be wired regardless of polarity.

## Customization

- Hyper illuminance xenon lamp type(model number: S150RHS/S150RHS-FT)

## Ordering Specification

S150RS	-	220	-	R
[Model number]		[Voltage]		[Color]
S150RL		12/24-DC12V-24V		● R-Red
S150RL-FT		110-AC110V		● A-Amber
S150RS		220-AC220V		● G-Green
S150RS-FT				● B-Blue