


MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SKMP/SKMPH				
MATERIAL			HOUSING-PC				
			LENS-PC				
			REFLECTOR-PC/SUS				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
REV. PER MIN.			120 ~ 140				
USE VOLT.	BULB	CURRENT	SKMP	DC12V	15W	MAX. 1.544A	
				DC24V		MAX. 0.766A	
			SKMPH	DC12V	35W	MAX. 3.077A	
				DC24V		MAX. 1.544A	
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3			±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SKMP/SKMPH OUTLINE DRAWING			MPSK/SKMPH		
			DWG. NO.		
			SKMP/SKMPH_OUT		
SCALE		SIZE	REV	SHEET	
N/S		A4	00	1/1	

A4(297X210)